

MÖLLER-CHEMIE STEINPFLEGEMITTEL GmbH  
 ZIEGELTALSTRASSE 2  
 D-93346 IHRLEINSTEIN  
 TELEFON 09441-176940  
 TELEFAX 09441-1769499  
 www.moellerstonecare.eu  
 info@moellerstonecare.eu



# MOELLER STONE CARE

## COMPOSITE-QUARTZ Floors

### TI-18.1

– *cleaning and maintenance* –  
*Care instruction tested*

#### CONDITIONS

When treating a newly laid surface ensure sufficient drying time for the moisture to escape from the surface and substructure (maximum 2-4% residual moisture content).

Allow 2-3 weeks drying time for an adhesive bed and 4-6 weeks for mortar bed.

Drying times are indicative only and are subject to variation depending on the weather and the object and can be longer.

It's essential that any under-floor heating has been switched off and the surface is at a normal temperature, adequately cleaned, free of stains, dry and absorbent.

Always test in an inconspicuous place to determine suitability and coverage. Always read the labels carefully. Ensure the area around the surface to be treated is well ventilated.

#### CLEANING

**Construction dirt:** R185 Composite Quartz Intensive Cleaner Coverage: approx. 20-60 m<sup>2</sup>/litre

**Stains:** Refer to Technical Information Sheet No. 1

After cleaning the surface must be allowed to dry for at least 1 to 2 days to a residual moisture content of 2-4% before any further treatment can take place.

#### PROTECTION – inside and outside

**Minimal colour enhancing:** S246 Composite Quartz Stain Protection Coverage: approx. 20-40 m<sup>2</sup>/litre

Once dry the residual material is not harmful to health.

#### MAINTENANCE – inside and outside

**Regular maintenance:** P311 Composite-Quartz Care Cleaner  
 add approx. 25 ml for every 10 liters of wash water

**Periodical intensive cleaning:** R185 Composite Quartz Intensive Cleaner  
 periodical if necessary do a cleaning with soft brush

#### OLD SURFACES

**Films of maintenance products and dirt:** R185 Composite Quartz Intensive Cleaner Coverage: approx. 20-60 m<sup>2</sup>/litre

**Layer of Waxes:** R154 Stripper - Stain Remover Coverage: approx. 5-10 m<sup>2</sup>/litre

**For optimum results and durability of further applications, older surfaces should be thoroughly cleaned. Repeat cleaning if necessary.** After necessary drying time is allowed, proceed with products indicated under „PROTECTION“. Always follow individual product directions.

#### ENVIRONMENT

All specialist products comply with the German Detergent Act and are registered with the Federal Environmental Offices in Berlin.

**Our specialized products have been recommended for decades by leading composite quartz tiles producers.**

This technical instruction card is for advice only and is supplied without obligation. We require that the person making the application adapts all data concerning the application of the products to local conditions and the materials to be cleaned. We reserve the right to make changes to our products without warning as a result of technological advancement. The person conducting the application is responsible for any third person liabilities and ensuring compliance with any local laws or regulations.

**All products are available  
 from many reputable natural  
 stone and tile dealers.**

Your local dealer: