

MÖLLER-CHEMIE STEINPFLEGEMITTEL GmbH
 ZIEGELTALSTRASSE 2
 D-93346 IHRLEINSTEIN
 TELEFON 09441-176940
 TELEFAX 09441-1769499
 www.moellerstonecare.eu
 info@moellerstonecare.eu

MOELLER STONE CARE



PRODUCT SPECIFICATION

HMK® P329 - TERRACOTTA WAX - brown

- **Special ready to use natural wax for terracotta, block paving and clay tiles.**
- **Enhances the color and shine and reduces water and dirt penetration.**
 - **For interior use only.**

HMK® P329 is a ready to use natural wax that enhances the color and shine of terracotta, clay and brick surfaces. HMK® P329 additives give the surface an antique and rustic appearance. Water and dirt penetration is reduced and surfaces become easier to maintain and more durable. For interior use only. Do not use in wet areas such as shower cabins.

Note: HMK® P326 Terracotta Care should follow the application of HMK® P329 to help blend in any HMK® P329 unevenness. Allow HMK® P329 to cure for 24 to 48 hours before applying HMK® P326 Terracotta Care.

Instructions: If under floor heating exists, switch it off and allow the surface to cool. Clean stone surface thoroughly and let it dry (max. residual moisture of 2-4%). Shake well before use. Add the brown coloring component until the desired appearance is achieved. Working on manageable areas at a time apply the mixture thinly and evenly with HMK® Z950-Z951 Application Brushes, a roller with short fibres, a white terry cloth or a soft brush and rub in gently and allow to dry. Once dry buff the surface either by hand using a soft cloth, a hand held polishing machine using a lambswool bonnet or a floor polishing machine with a white/tan polyester pad. Repeat the treatment for very absorbent surfaces. To maintain the appearance, repeat the treatment in accordance with usage but at least once per year.

To clean surface thoroughly before treatment and to periodically refresh the surface use HMK® R155 Intensive Cleaner - acid free.

For regular cleaning and continued protection use HMK® P324 Liquid Stone Soap, a no-rinse natural product and HMK® P326 Terracotta Care.

Important: Do not walk on the treated surface until the procedure is completed. Do not apply to rubber, plastic, lacquered, waxed or varnished wood and solvent-intolerant surfaces.

Coverage: About 5-10m² per litre.

Warning: Chemical product. Flammable. Contains Turpentine Substitute. Keep away from heat, sparks and flame. Harmful or fatal if swallowed or inhaled. Ensure adequate ventilation during the application process. Avoid eye/skin contact and breathing vapour or mist. If exposed flush/wash with water and seek medical attention. Keep container closed and out of the reach of children.

Packaging: 12 x 1 litre bottles/box.

Storage: Store in a cool place and ensure the lid is kept tightly closed.

Testing: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12° and above 25°C.

Limitation of liability: The liability of HMK® Moeller Stone Care for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stone Care shall not be liable for any consequential damages. No other warranty or representation is made or implied.